



# FICHE DE CARACTERISTIQUES WEBBING CHARACTERISTICS

Modification 15/09/2017

Code Article at Lorentzen

## 4521425R2

TEINTURE / DYEING

### Identification

ECRU TEP PES UNI - RAIDE

TE

ACTIF



Description:

Processing:	APPRET	Special:	RAIDE
-------------	--------	----------	-------

### Caractéristiques

Width (m/m): <b>25,00</b> / - 1,00 / + 1,00	Thickness (m/m): <b>2,00</b> / - 0,50 / + 0,50	Weight (g/m): <b>37,00</b> / - 1,20 / + 1,20	Breaking strength (daN): <b>2 000</b>
Weaving construction: Taffetas Tub Lié		Material: POLYESTER	T° fusion: 250 °C

-  
-

-  
-

Flame Resistance:

INFLAMMABLE  
FLAMMABLE

Resistance to chemicals:

Acide/Acids BONNE / GOOD  
Bases/Alkali MOYENNE / MEDIUM

Toxicity:

AUCUNE  
NONE

Rotting:

AUCUNE  
NONE

Solidité Frottement / Colour fastness:

RISQUE DE DEGORGEMENT  
LOW

Note: These characteristics are given as part of the specification and may be modified to accomodate additional requirements.