



LIROS Dynamic Color / Plus 02028 / 02004


Easy-handling, abrasion resistant line with low stretch, premium Polyester cover and Dyneema® SK78 core. Suitable for use as a highend sheet, or low-stretch halyard by advanced cruising sailors.

- working stretch < 2%
- kink-free, low-stretch sheets for cruiser-racers
- easy to splice
- LIROS Heat-Stretch-System




LIROS HSS
with LIROS Heat-Stretch-System
LIROS LCS
with LIROS Coating-System

Colours 02028



021
Blue-White
067
Yellow-White
092
Green-White
179
Red-White
775
Dark Grey-White

Colours 02004



228
White
229
White-Blue
231
White-Yellow
232
White-Green
236
White-Red

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
3	500	7	250
4	710	11	250
5	870	17	250
6	1200	21	200
8	2300	38	200
10	3100	69	200
12	4800	89	200
14	6500	119	150

Cover

Polyester high twisted

Construction

3–5 mm 16-plaited
6–8 mm 24-plaited
10mm and up 32-plaited

Core

Dyneema® coated,
6mm and up with additional cover plait

LIROS Max Load System (MLS)

LIROS MLS crafted halyards and sheets for all popular boat sizes. Regatta ready, manufactured to exact LIROS standards. LIROS MLS with integrated shackle comes in a handy MLS mesh stow bag.

- Premium workmanship
- Product information see above



LIROS HSS
with LIROS Heat-Stretch-System
LIROS LCS
with LIROS Coating-System

Colours



021
Blue-White



179
Red-White

Halyard (Main, Genoa, Spi)



Reference	Ø mm	Length m	Attachment / halyard shackle	Breaking strength kg	Boat Size ft
02028-0830	8	30	pilot eye / spliced Wichard 81433	1800	22–29
02028-1035	10	35	pilot eye / spliced Wichard 81434	2400	30–36
02028-1240	12	40	pilot eye / spliced Wichard 81434	3800	37–42

Sheet (Spi, Genoa)

Reference	Ø mm	Length m	Attachment / snap shackle	Breaking strength kg	Boat Size ft
02028-0825	8	25	whipping / spliced Wichard 2473	1800	22–36
02028-1025	10	25	whipping / spliced Wichard 2475	2400	37–40
02028-1230	12	30	whipping / spliced Wichard 2475	3800	40–42



LIROS D-Pro

01505

LIROS Heat-Stretch-System guarantees optimal breaking loads and stretch characteristics of this line. Excellent chafing resistance, light weight, and easy spliceability make this line irreplaceable in all sorts of applications on racing boats of any size. Perfect as a replacement for steel cabling in technical applications.

- working stretch < 1 %
- very high breaking load with small diameter and very low weight
- first choice for any application under extreme loads
- very spliceable
- highly UV stable and chafe resistant
- LIROS Heat-Stretch-System


Material Coated Dyneema® SK78

Construction 12-plaited, heat-set and coated



Not certified for lifting loads and personal security!

Colours



010
Blue




171
Red



228
White



059
Yellow



205
Silver



674
Deep Black (2 and up)



LIROS D-Pro Vision

01508

The new LIROS D-Pro Vision made of 100% Dyneema® SK78 with extremely high breaking loads at lowest weight! Best differentiation in all applications – whether as high-strength winch rope in industrial use or as universally useable watersports line. High UV-stability combined with best abrasion resistance and highest breaking loads at lowest weight guarantee best safety in practical use. First choice for replacing steel ropes in sports and industrial use.

- working stretch < 1 %
- very high breaking load with small diameter and very low weight
- first choice for any application under extreme loads
- very spliceable
- highly UV stable and chafe resistant
- LIROS-Heat-Stretch-System

Ø mm	Breaking strength kg	Weight g/m	Length of spool m
3	950	4,6	100
4	1300	7	100
5	2600	13	100
6	4300	23	100
8	5300	35	100
10	9000	60	100



Material
Coated Dyneema® SK78

Construction
12-plaited, heat-set and coated

Colours



019
Blue-Black



065
Yellow-Black



178
Red-Black