


The market reference  
for a multipurpose  
technical cover



**Traffic white**


RAL 9016 - 705-1066



Traffic white  
RAL 9016 705-1066



Light ivory  
RAL 1015 705-1076




Carmine red  
RAL 3002 705-1065



Ultramarine blue  
RAL 5002 705-1051



Sky blue  
RAL 5015 705-1053



Moss green  
RAL 6005 705-50201




Opal green  
RAL 6026 705-1055




Light grey  
RAL 7035 705-1069



Dusty grey  
RAL 7037 705-1070



Agate grey  
RAL 7038 705-1071



Window grey  
RAL 7040 705-1072



Jet black  
RAL 9005 705-1075

# Protect

## Cover 705

### Main applications

- Wide range of applications
- Truck covers
- Flexible roll-up doors

### Major advantages

- High dimensional stability thanks to Precontraint® technology
- Excellent lifespan and flatness
- High UV resistance
- Excellent weldability
- Wide colour range in stock
- Anti-theft option with Protect Secure product range

	■ Technical properties	Standards
Coating at top of yarns	261 microns	
Total thickness	0.57 mm	
Yarn	1100 dtex PES HT	
Weight	670 g/m <sup>2</sup>	EN ISO 2286-2
Width	270 cm	
Finish	Varnish both sides	
Standard format length	rolls: 30 lm - jumbo rolls: 350 lm	
	■ Physical properties	
Tensile strength (warp/weft)	250 / 250 daN / 5 cm	EN ISO 1421
Tear strength (warp/weft)	25 / 25 daN	DIN 53.363
Extreme working temperatures	-30° C / +70° C	
Provided services	Width reduction service - Width/length adjustment Cut length - Slitting	
	■ Management systems	
Quality		ISO 9001
Environment		ISO 14001
Energy		ISO 50001
	■ Certifications, labels, guarantees	

### Precontraint technology

The technical data above are averaged values with a +/- 10% tolerance. The buyer of our products is fully responsible for their application or their transformation concerning any possible third party. The buyer of our products is responsible for their implementation and installation according to the standards, use and customs and safety rules of the countries where they are used. For information on our contractual warranty, please refer to the relevant terms and conditions. The values quoted above represent results of tests performed in compliance with common design practices and are provided for only to enable customers to make the best use of our products. Our products are subjects to evolutions due to technical progress, we remain entitled to modify the characteristics of our products at any time. The buyer of our products is responsible for checking the validity of the above data.